FIG. 1 (Prior Art)



Pentium II, III Branch Target Buffer

FIG. 2 (Prior Art)



200

Athlon BTAC Integrated into Instruction Cache

FIG. 3



Processor Pipeline Stages

FIG. 4



Speculative Branch Prediction Apparatus

FIG. 5



Instruction Cache

FIG. 6


way 0
way 1
way 2
way 3
A
B
614
612
495
virtual address tags
616
602
comparators 604
way mux 606
618
452
624
626
control logic 404
A/B mux 608
622
352, 454
402
BTAC

FIG. 7



602

BTAC Entry

FIG. 8



Speculative Branching Operation

FIG. 9



Target Address Selection Example

FIG. 10



Detection and Correction of
Speculative Branch Misprediction

FIG. 11

Previous Code Sequence:

0x00000010 JMP 0x00001234
...

Current Code Sequence:

0x00000010 ADD ;address 0x00000010 hits in BTAC generating a TA value of 0x00001234
...

0x00001234 SUB
0x00001236 INC

clock →	1	2	3	4	5	6	7
I-stage	ADD	X	X	SUB	INC	X	ADD
B-stage		ADD	X	X	SUB	X	X
U-stage			ADD	X	X	X	X
V-stage				ADD	X	X	X
F-stage					ADD	X	X

Cycle 1 = BTAC and I-cache access cycle
Cycle 4 = speculative branch cycle
Cycle 5 = speculative branch error detection cycle
Cycle 6 = BTAC invalidate cycle
Cycle 7 = speculative branch error correction cycle

1100

Misprediction Detection and Correction Example

FIG. 12



Hybrid Speculative Branch Direction Predictor

FIG. 13



Dual CALL/RET Stack Operation

FIG. 14



Selective Override of BTAC Prediction Operation

FIG. 15



BTAC A/B Replacement Apparatus

FIG. 16



A/B Entry Replacement Method

FIG. 17



A/B Entry Replacement Method (Alt. Embodiment)

FIG. 18



BTAC A/B Replacement Apparatus (Alt. Embodiment)

FIG. 19



BTAC A/B/C Replacement Apparatus